Applicant Initiated Interview Request Form - faxed to: 571. 270. 8655 (3 pp.)

In re the Application of Akio ENOMOTO et al. Group Art Unit: 1746

Examiner: J. RIVERA

Application No.: 10/591,296
Filed: August 31, 2006

Docket No.: 129280

For: FILM BONDING MACHINE

Tentative Participant	s:	(2) Examiner Rivers	a		
(3)		(4)			
Confirmed Date of In	terview: April 13, 2011	Proposed Time	: 11:00 AM	(A)	1/PM)
Type of Interview Requested: (1) ☐ Telephonic (2) ☑ Personal (3) ☐ Video Conference					
Exhibit To Be Shown or Demonstrated: YES NO If yes, provide brief description:					
	Iggue	s To Be Discusse			
Issues (Rej., Obj., etc)	Claims/ Fig. #s	Prior Art	Discussed	Agreed	Not Agreed
(I) §103(a) Rej.	1, 4-9 and 11	Fukuta, Onodera, Yamamura and Kanchara			
(2)					
(3)			. 🗆		
Continuation Sheet Attached					
Brief Description of A	Arguments to be Presented:				
The stripping section of Yamamura does not correspond to the winding element of claim 1. Also, the references would not have rendered obvious the features of claims 12 and 13 in the attached Appendix.					
An interview was conducted on the above-identified application on					
NOTE:					
This form should be co	mpleted by applicant and subn	nitted to the examiner in	advance of the inte	rview (see MI	PEP § 713.01).
This application will not be delayed from issue because of applicant's failure to submit a written record of this interview. Therefore, applicant is advised to file a statement of substance of this interview (37 CFR 1.133(b) as soon as possible.					
(Applicant/Applicant's Representative Signature)			(Examiner/SPE Signature)		

APPENDIX

- 1. (Currently Amended) A film bonding machine comprising:
- a honeycomb structural body mover capable of gripping and moving a honeycomb structural body to an intended location;
- a tape bonder that bonds a-an uncut tape onto an end surface of the honeycomb structural body;
- a laser oscillator that oscillates a laser so as to perform cutting processing of the tape bonded onto the end surface of the honeycomb structural body to obtain the honeycomb structural body wherein the tape having a predetermined size along an outer peripheral shape is bonded on the end surface;
- a moving type or tilt type mirror located in a position capable of reflecting a light reflected from the tape bonded to the end surface of the honeycomb structural body on the same axis as the laser oscillated from the laser oscillator and capable of being moved from the position on the same axis when the laser oscillates;
- an image pick-up unit that picks up an image of the end surface of the honeycomb structural body reflected by the mirror, and
- a processing position controller that positions the laser from the laser oscillator so as to cut the bonded tape into an intended shape based on the picked image.
- wherein the tape bonder includes a winding element for winding a residual portion of the tape that is created after the tape is cut to leave the cut portion as a masking for non-pluseing cells on the end surface of the honeycomb structure by the laser oscillator.
- (New) A film bonding machine according to claim 1, further comprising a draw-out portion.

 (New) A film bonding machine accroding to claim 1, further including a press unit.